

## DECLARATION OF PERFORMANCE

**N. DoP19/0509**

### Point

|  |   |
|--|---|
| 1. Unique identification code of the product-type          | Point 19/0509   |
| 2. Intended use/es   | impact sound insulation   |
| 3. Manufacturer  | ISOLGOMMA S.r.l. - Via Dell'Artigianato, 24<br>36020 - Albettono (VI) - Italia  |
| 5. System/s of AVCP  | System 3  |
| 6. European Assessment Document                            | EAD 040048-01-0502 Rubber fibre mat<br>to be used for impact sound insulation   |
| European Technical Assessment<br>Technical Assessment Body | ETA 19/0509<br>ITC-CNR Istituto per le Tecnologie della Costruzione<br>Via Lombardia, 49 - San Giuliano Milanese (MI) |
| Notified body/ies  | -   |
| 7. Declared performance                                    | see table below   |

| N.  | Essential characteristic                         | Unit | Performance          |
|-----|--|------|----------------------|
| 1.  | Reaction to fire                                 |      | E <sub>fl</sub>      |
| 2.  | Content and/or release of dangerous substances   |      | NPD                  |
| 3.  | Dynamic stiffness                                |      | NPD                  |
| 4.  | Impact sound reduction                           | dB   | $\Delta L_w = 28$    |
| 5.  | Geometry: - Length                               | mm   | 1000 - L3            |
|     | Geometry: - Width                                | mm   | 1200 - W3            |
|     | Geometry: - Deviation from squareness            | mm/m | S <sub>b</sub> = 4,2 |
| 6.  | Thickness  | mm   | dL = 18 ± 10%        |
|     | Compressibility                                  | mm   | c ≤ 2,2              |
| 7.  | Mass per unit area                               |      | NPD                  |
| 8.  | Compressive creep                                |      | NPD                  |
| 9.  | Compressive stress/strength                      |      | NPD                  |
| 10. | Deformation under specified load and temperature |      | NPD                  |
| 11. | Resistance to breaking or cracking               |      | NPD                  |
| 12. | Thermal resistance                               |      | NPD                  |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Albettono, 22/01/2020

Signed for and on behalf of the manufacturer by:

  
 .....  
 Fabio Loriggiola (R. & D. Engineer)