



### BENEFITS

- Completely closed cell
- Fine, regular cell structure
- Good mechanical properties
- Excellent thermal insulating
- Permanently elastic
- Minimal water absorption
- Very low water vapour permeability
- Good resistant to most chemicals
- Permanently resilient
- Environmentally friendly
- Non-toxic
- Does not contain CFCs
- Good adhesion

## SIREX PE C100

SIREX PE C100 is a closed-cell chemical cross-linked PE foam with a density of approx. 100 kg/m<sup>3</sup>. Standard size of a base block is approx. 2000 x 1000 x 53 mm.

### PROCESSES AND APPLICATIONS

SIREX PE C100 is available in the desired thickness and shape. For example, the following processing techniques can be applied to the material: skiving, laminating, cutting, punching, milling, water-jetting, laser, butt welding, self-adhesive and thermoforming.

### Some applications of the SIREX PE C100 are:

Industrial gaskets, insulation, boat fenders, (presentation) packaging, cutting – punching parts and water play equipment.



ISMt B.V.  
Küppersweg 18  
NL - 2031 EC Haarlem



Niederlassung Deutschland  
Ludwig-Herr-Str. 23  
D - 70806 Kornwestheim



+31 (0)88 018 4900  
+49 (0)7154 3091



www.ismt-bv.com  
sales@ismt-bv.com

**TECHNICAL INFORMATION**

PROPERTIES	NORM	UNIT	VALUE
<b>Thickness</b>	IE-03	mm	53 ± 3
<b>Length</b>	IE-03	mm	≥ 2000
<b>Width</b>	IE-03	mm	≥ 1000
<b>Density</b>	IE-04	kg/m <sup>3</sup>	100 ± 15
<b>Cell size</b>	IE-09	mm	0,21
<b>Elongation at break</b>	IE-06	%	169
<b>Tensile Strength</b>	IE-06	kPa	803
<b>Compression strength</b>	IE-05		
10% compression		kPa	205
25% compression		kPa	240
50% compression		kPa	361
<b>Compression Set, 25%, 22 h</b>	IE-07		
0,5 h recovery		%	6
24 h recovery		%	2
<b>Shore hardness</b>	IE-08	∞	≥ 76
<b>Water Absorption (28 days)</b>	DIN 53428		
vol% water absorption		%	1
<b>Maximum working temperature</b>	IE-02	°C	105
<b>Thermal conductivity</b>	ISO 2581		
at 10 °C		W/mK	0,045
at 40 °C		W/mK	0,048
<b>Flammability thickness 10 mm</b>	ISO 3795	mm/min	≤ 100

The internal norms IE-03, IE-04, IE-05, IE-06 and IE -07 are based by standards ISO 1923, ISO 845, ISO 844, ISO 1926 and ISO 1856-B, respectively.